

1. Before you hit the road...

- Close fridge door properly;
- Ensure all 12 volt switches, except the fridge switch, are turned off;
- Store utensils and microwave plate;
- Disconnect appliances and place in cupboards;
- Close and secure any doors, drawers, windows, skylights or vents. Retract awning;
- Retract outside step if fitted;
- Turn off gas bottle and grey water tap;
- Disconnect all hoses and electricity cable;
- Look for obstacles outside vehicle before leaving;
- Use a spotter when reversing;
- Lock fresh water cap and exterior compartments.

2. When arriving at a camp site

Battery System

- Ensure 240 volt main switch circuit breaker is in the 'ON' position;
- The main switchboard operates items that run on the 12V house battery;
- Important – microwave, living cabin air-conditioner and power points require electricity to be connected to mains power;
- House battery is only charged when plugged into mains power or when the vehicle is travelling. Driving the vehicle or leaving the engine to idle will not provide sufficient charge to fully charge the house battery;
- When the house battery is fully charged the battery gauge will read 14V. This should be sufficient power for 12-20 hours, depending on use e.g. fridge on low setting, limiting opening and closing of fridge, no excessive use of lights.

We strongly recommend that the vehicle is plugged into mains power every 24-48 hours MAXIMUM to ensure the auxiliary battery is kept well charged

Television

- Re-tune the TV for each area you stop at;
- Press 'MENU' on the television remote and navigate to TV channel auto tune. This may take a few minutes.

There are several locations throughout Australia and New Zealand where there is little to no television reception.

Stove

- Turn on gas bottle (outside);
- Ensure adequate ventilation;
- Turn on 'Cooker Ignition' or 'Rangehood Switch' on main switchboard;
- Turn gas knob to large flame symbol, push knob in and click igniter or light with a match;
- When lit, keep pushing on gas knob for further 10 seconds;
- Turn on Range Hood.

Bed Conversion

Rear Bed Conversion

- Loosen lever under centre of table, lift table up and off;
- Loosen lever on table leg, then slide leg assembly up and stow;
- Lay table top between seats on ledge;
- (For Tourer and Hitop, lay second bed board from behind driver's seat next to table top);
- Arrange cushions to form the bed.

If you are experiencing mechanical difficulties call 1300 798 212 (AU) or 0800 234 567 (NZ)

Front Bed Conversion

- Press the buttons down that connect the table top to the interior wall;
- Lift the table off the wall bracket;
- Squeeze the top of the table leg together and fold up and under the table top;
- Lay table top between seats on ledge;
- Pull the bed supports out into the aisle;
- Remove the long rectangular cushion from the sleeping area over the driving cabin;
- Arrange cushions to form the bed.

Water Tank

- Top up regularly using supplied hose, do not use at high pressure;
- Feed hose about 6 inches/15cm into inlet before turning tap on;
- Stay with the vehicle while filling;
- Replace hose when finished, secure and lock water cap.

We cannot guarantee the quality of the water. Either boil the water for drinking or use bottled water.

Hot Water

- Please follow the sequence below or the hot water will malfunction:
- Open the connected gas bottle (outside);
- Ensure the water tank is at least ¼ full;
- Turn on 'Hot Water' and 'Water Pump' on main switchboard;
- Turn on the hot water ignition switch located below main switch panel.

If a red light comes on (on the hot water ignition switch) after 30 seconds, the unit has failed to light. Turn off the above 3 switches and repeat.

Cold Water

- Ensure the water tank is not empty;
- Turn on 'Water Pump' on main switchboard.

Toilet

- Ensure the toilet water tank (located either above the toilet cassette or draws from main water tank) is not empty;
- Turn on 'Water Pump' and 'Toilet' on main switchboard;
- Turn lever on side of toilet to open before use;
- Flush as normal;
- Close lever on side of toilet after use.

Toilet Waste

- Waste cassette is on driver's side of vehicle;
- **ENSURE TOILET LEVER INSIDE VEHICLE IS CLOSED;**
- Release clip under cassette and slide unit out;
- **ONLY DUMP WASTE INTO TOILETS OR APPROVED WASTE STATION;**
- Rotate spout, remove cap and tip to release waste;
- Rinse inside and outside of cassette and add a new chemical sachet along with a little water;
- Replace cap tightly and slide cassette back into cassette cavity;

Grey Water

- Empty grey water tank each time you fill up the fresh water tank;
- Use the large grey water hose supplied and connect to grey water outlet under vehicle;
- Place the other end of the hose into approved waste outlet;
- Turn tap parallel to pipe to open;
- When finished turn grey water tap off;
- Disconnect hose, rinse and return to vehicle.

If you are experiencing mechanical difficulties call 1300 798 212 (AU) or 0800 234 567 (NZ)